

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (*Currently amended*) A data contents processing method, comprising ~~the steps for~~:

separating audio/video (A/V) signals and data contents upon receipt of a broadcast signal and extracting information on ~~the currently received~~ a current channel and a program identifier;

constructing a database by forming an integrated information of a channel/program identifier information and data contents in connection with each other;

controlling the conversion of data contents by checking whether or not the data contents to be displayed are consistent with the current A/V signal according to the integrated information; and

when the data contents ~~is~~ are converted to thus select a user-desired data contents, displaying the A/V signal and the data contents,

wherein the conversion of data contents includes displaying a different data contents and conversion of the channel includes changing to a different channel.

2. (*Currently amended*) The method according to claim 1, wherein the controlling step further comprises ~~the step for~~ controlling a channel conversion.

3. (*Currently amended*) The method according to claim 1, wherein, in the controlling step, when the user converts the current channel to a new channel using a channel converter, ~~the~~ data contents corresponding to the new converted channel are selected.

4. (*Currently amended*) The method according to claim 1, wherein, in the controlling step, when user-desired data contents are selected by means of ~~the forward/backward function of the~~ a browser for controlling data contents, the current channel is tuned in to ~~the~~ a new channel corresponding to the selected data contents.

5. (*Currently amended*) The method according to claim 1, wherein the displaying step further comprises ~~the step for~~ displaying only the broadcast channel corresponding to the A/V signal.

6. (*Currently amended*) The method according to claim 1, wherein the data contents processing method further comprises: ~~the step for~~ adjusting a channel so as to display A/V signals or A/V signals and data contents, or ~~the step for~~ inputting a user command signal corresponding to ~~the~~ a forward/backward function of ~~the~~ a browser.

7. (*Currently amended*) A data contents processing method, comprising ~~the steps for~~:

separating audio/video (A/V) signals and data contents upon receipt of a broadcast signal of a bit stream and extracting information on ~~the~~ a current channel of the broadcast signal corresponding to the bit stream and a program identifier;

constructing a database by forming an integrated information of a channel information, program identifier, and data contents in connection with one another;

judging whether or not the data contents to be displayed and the current A/V signal are consistent with each other according to the integrated information; and

if the data contents to be displayed are not consistent with the current A/V signal according to the integrated information, displaying the A/V signal

and the received data contents ~~being consistent with each other~~ upon receipt of the data contents corresponding to the A/V signal.

8. *(Original)* The method according to claim 7, wherein, in the displaying step, if the data contents to be displayed are consistent with the current A/V signal according to the integrated information, the A/V signal and the corresponding data contents are displayed.

9. *(Currently amended)* The method according to claim 7, wherein, in the displaying step, if the data contents corresponding to the A/V signal cannot be received again, ~~the~~ a message that the A/V signal cannot be displayed_{[[,]]} or ~~the~~ a function of ~~the~~ a browser is not operable is displayed.

10. *(Currently amended)* The method according to claim 7, wherein the step ~~for~~ of judging whether or not the data contents are consistent with the current A/V signal further comprises ~~the step for:~~

controlling the channel and ~~the~~ a browser according to a user's request_{[[,]]} and

storing the A/V signal and data contents from the corresponding channel and site.

11. (*Currently amended*) The method according to claim 7, wherein, ~~in the step for judging whether or not the data contents~~, if the a browser function is not operated, only the A/V signal is displayed.

12. (*Currently amended*) ~~A data contents processing method, comprising the steps for~~ An apparatus for data contents processing, comprising:

an inverse multiplexing unit configured for separating audio/video (A/V) signals and data contents upon receipt of a broadcast signal of a bit stream and extracting information on the a channel of the broadcast signal corresponding to the bit stream and a program identifier;

a database constructing unit configured for constructing a database by forming an integrated information of a channel information, program identifier, and data contents in connection with one another;

an A/V interface control unit configured for judging whether or not the data contents to be displayed and the current A/V signal are consistent with each other according to the integrated information; and

a browser unit configured for displaying to a display unit the current A/V signal and the database contents,

wherein if the A/V interface control unit judges that the data contents to be displayed are not consistent with the current A/V signal according to the

integrated information, the browser unit displays to the display unit ~~displaying~~
the A/V signal and the received data contents ~~being consistent with each other~~
upon receipt of the data contents corresponding to the A/V signal.

13. *(Original)* The apparatus according to claim 12, wherein the browser unit further comprises a forward/backward function.

14. *(Original)* The apparatus according to claim 12, wherein the display unit displays the A/V signal outputted from the inverse multiplexing unit.

15. *(Original)* The apparatus according to claim 12, wherein the database constructing unit further comprises a storage unit for storing the separated data contents.

16. *(Original)* The apparatus according to claim 12, wherein the integrated information is a tree data structure in which a plurality of programs corresponding to one channel are connected to the channel, and a plurality of data contents corresponding to each program are connected to the program.

17. *(Currently Amended)* The apparatus according to claim 12, wherein, when the user converts the channel using a channel conversion key, the A/V

data interface control unit checks whether or not the currently displayed data contents are the data contents corresponding to the converted channel according to the integrated information, and, if the currently displayed data contents are not the data contents corresponding to the converted channel, it the A/V data interface control unit controls the browser to select the data contents corresponding to the converted channel.

18. (*Currently amended*) The ~~method~~ apparatus according to claim 12, wherein, when the user selects data contents by means of ~~the~~ a forward/backward function of the browser, the A/V data interface control unit checks whether or not the currently displayed channel corresponds to the selected data contents according to the integrated information, and, if the channel does not correspond to the selected contents, ~~it~~ the A/V data interface control unit controls the inverse multiplexing unit to tune in to the channel corresponding to the selected data contents.

19. (*New*) The method according to claim 4, wherein a forward/backward function of the browser is used to select the data contents.

20. (*New*) A data content processing method comprising:
receiving a bit stream of a broadcast signal;

separating audio/video (A/V) signals from data contents from the bit stream of a selected channel;

upon receipt of a channel change request, determining whether current data contents correspond to the requested channel and changing the data contents to correspond to the requested channel if it is determined that the current data contents do not correspond to the requested channel, wherein the requested channel becomes the selected channel;

upon receipt of a data content change request, determining whether a current channel corresponds to the requested data content change and changing the channel to correspond to the requested data content change if it is determined that the current channel does not correspond to the requested data content change, wherein the changed channel becomes the selected channel; and

displaying A/V signals and corresponding data contents of the selected channel.

21. *(New)* The method of claim 20, wherein in the displaying step, if a browser unit is not operating, displaying the A/V signals of the selected channel only.

22. *(New)* The method of claim 20, wherein upon receipt of the data content change request, the method further comprises:

determining whether the requested content is in a local storage;

retrieving the requested content from the local storage if it is determined that the requested content is in the local storage; and

retrieving the requested content from the received bit stream if it is determined that the requested content is not in the local storage.

23. *(New)* The method of claim 22, wherein if the requested content is not in the local storage and the requested content cannot be retrieved from the received bit stream, the method further comprises displaying a message indicating that the requested content cannot be displayed.

24. *(New)* The method of claim 20, further comprising constructing a database of integrated information of channels and corresponding data contents from the received bit stream.

25. *(New)* The method of claim 24, wherein the step of determining whether current data contents correspond to the requested channel change, is performed based on the database of the integrated information.

26. *(New)* The method of claim 24, wherein the step of determining whether the current channel corresponds to the requested data content change, is performed based on the database of the integrated information.

27. *(New)* An apparatus to perform data content processing, comprising:

an inverse multiplexer configured for receiving a bit stream of a broadcast signal and for separating audio/video (A/V) signals from data contents from the bit stream of a selected channel;

a browser configured for controlling display of the data contents;

a data interface unit configured for:

upon receipt of a channel change request, determining whether current data contents correspond to the requested channel and changing the data contents to correspond to the requested channel if it is determined that the current data contents do not correspond to the requested channel, wherein the requested channel becomes the selected channel; and

upon receipt of a data content change request, determining whether a current channel corresponds to the requested data content change and changing the channel to correspond to the requested data content change if it is determined that the current

channel does not correspond to the requested data content change, wherein the changed channel becomes the selected channel; and a display unit for displaying A/V signals and corresponding data contents of the selected channel.

28. *(New)* The apparatus of claim 27, wherein if the browser unit is not operating, the display unit is configured for displaying the A/V signals of the selected channel only.

29. *(New)* The apparatus of claim 27, wherein upon receipt of the data content change request, the data interface unit is configured for:

determining whether the requested content is in a local storage;

controlling the browser to retrieve the requested content from the local storage if it is determined that the requested content is in the local storage; and

controlling the browser to retrieve the requested content from the received bit stream if it is determined that the requested content is not in the local storage.

30. *(New)* The apparatus of claim 29, wherein if the browser determines that the requested content is not in the local storage and the requested content cannot be retrieved from the received bit stream, the data

interface unit is configured for controlling the display unit to display a message indicating that the requested content cannot be displayed.

31. *(New)* The apparatus of claim 27, further comprising a database constructing unit configured for constructing a database of integrated information of channels and corresponding data contents received from the inverse multiplexer.

32. *(New)* The apparatus of claim 31, wherein the data interface unit determines whether current data contents correspond to the requested channel change based on the database of the integrated information.

33. *(New)* The apparatus of claim 31, wherein the data interface unit determines whether the current channel corresponds to the requested data content change based on the database of the integrated information.